

DESCRIPTION

The SR-S4SWP is a two-way line array speaker ideal for short distance sound transmission and configures a line array by arranging speaker elements vertically close to each other. It satisfies the water protection requirements set down in the IPX4 Standard. It can be converted into the bi-amplifier drive system by changing the internal connection. It can be used for high-impedance applications with the installation of the optional MT-S0601 Matching transformer.

SPECIFICATIONS

| | |
|-------------------------|---|
| Enclosure | Sealed type |
| Power Handling Capacity | Continuous program: 600 W (single-amp mode) Low 240 W, High 240 W (bi-amp mode) |
| Rated Impedance | 8 Ω (single-amp mode) Low 8 Ω, High 8 Ω (bi-amp mode) |
| Sensitivity | 93 dB (1 W, 1 m) |
| Frequency Response | 70 Hz – 20 kHz (when recommended parameters are applied by the optional DP-SP3) |
| Crossover Frequency | 3.5 kHz |
| Directivity Angle | Horizontal: 90°, Vertical: 10° |
| Speaker Component | Low frequency: 10 cm cone-type × 8 High frequency: 2.5 cm balanced dome-type × 24 |
| Connected Cable | Direct cable withdrawal from internal speaker: Ø8.6 mm, conductor cross section: 1.25 mm ² , 4-core cable, 3 m |
| Operating Temperature | -10 °C to +50 °C |
| Water Protection | IPX4 |
| Finish | Enclosure: Plywood, white, urethane coating Front grille: Punched stainless steel, white, paint |
| Dimensions | 160 (W) × 892 (H) × 303 (D) mm (excluding connected cable) |
| Weight | 16 kg |
| Accessory | Bi-amplifier drive rating label ...1, Bi-amplifier drive input indication label ...1 |
| Option | Matching transformer: MT-S0601, Extension plate: SR-EP4WP, Wall tilt bracket: SR-TB4WP, Protection pad: SR-PP4, Digital speaker processor: DP-SP3 |

APPEARANCE

